



Model Name	VL710	VL715/VL718/VL722			VL724	
Motherboard	D36	D36	D66	D35	D66	
CPU Supports	Intel Bay Trail J1900, Quad core 2G/2.41G		Intel® Haswell CPU (max. 45W)	Intel Bay Trail J1900, Quad core 2G/2.41G		Intel® Haswell CPU (max. 45W)
Chipset	CPU integrated		Intel Q87 (AMT 9.0)	CPU integrated		Intel Q87 (AMT 9.0)
System Memory	DDR3L 1333MHz (max. 8GB)		DDR3 1333MHz (max. 8GB)	DDR3L 1333MHz (max. 8GB)		DDR3 1333MHz (max. 8GB)
Memory Socket	1 x SO-DIMM					
Graphic Memory	Intel HD Graphic					
Display & Touch Panel						
LCD Size	10.1"	VL715: 15.6", VL718: 18.5", VL722: 21.5"			24"	
Brightness	200 cd/m ²	VL715: 220 cd/m ² , VL718: 250 cd/m ² , VL722: 250 cd/m ²			250 cd/m ²	
Maximal Resolution	1366 x 768	VL715: 1366x768, VL718: 1366x768, VL722: 1920x1080			1920 x 1080	
Touch Screen Type	True flat RES touch / True flat P-CAP touch				True flat P-CAP touch	
Storage Device						
HDD/SSD	1 x 2.5" SATA bay					
Flash Memory	SATA Slim SSD 8G / 16G / 32G / 64G (option)					
Expansion						
Mini-PCIE Socket	1					
External I/O Ports						
USB 3.0	1	1	2	N/A	2	
USB 2.0	4					
Serial / COM	3 (RJ-48) (with DB9 convert cable)		4 (RJ-48) (with DB9 convert cable)		2 (DB9)	4 (RJ-48) (DB9 converter)
LAN (10/100/1000) Mbps	1	2				
Audio Jack	N/A	1 x Line-out		1 x Line-out & 1 x Mic-in		
VGA	1			N/A		
DVI	N/A	DVI-D x 1		DVI-I x 1		DVI-D x 1
Power Button	1					
Audio						
Internal Speaker	2 x 2W			2 x 3W		
Power						
Input Voltage	19V	12-48V				
Connector	4-pole DIN (with latch)					
Power Adapter	65W	K757/K758: 65W, K759: 90W	120W	90W	120W	
Peripherals (option)						
Webcam (Build in)	2M			5M		
WiFi	802.11 b/g/n WLAN card + BT 4.0					
MSR	3 tracks (USB)					
Device Box	Smart IC card Reader / RFID / Scanner / Function Keypad / Line Out / Mic In					
Certificate						
EMC & Safety	FCC Class A / CE / LVD			FCC Class B / CE / LVD		FCC Class A / CE / LVD
Medical	EN 60601-1/UL60601-1 3rd	N/A			EN 60601-1/UL60601-1 3rd	
Environment						
Ventilation	Fanless		Fan	Fanless		Fan
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F) (Still Air)					
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)					
Humidity	20% ~ 85% RH non-condensing					
Dust & Water Proof	Front IP65					
Dimension (WxDxH)	263 x 38 x 170 mm	VL715: 396 x 48 x 245 mm, VL718: 464 x 48 x 284 mm VL722: 536 x 48 x 328 mm			588 x 50 x 365 mm	
Weight	1.5kg	VL715: 4.5kg, VL718: 6.8kg, VL722: 8kg			8kg	
Mounting	VESA 75				VESA 100	
OS Supported	Windows 7 (32/64 bit), Windows 8.1 (32/64bit), Linux					