

HC100™ Wristband Printer

Easiest Way to Print Wristbands On-demand



Simple to Use

Zebra's HC100 printer was developed to maximize ease of use. There's minimal training required. Just pop the easy-to-load cartridges containing Zebra's Z-Band® wristbands into the printer—and print individual wristbands.

The HC100 printer detects the wristband size and automatically calibrates its settings for optimal print quality. You get long-lasting wristbands with bar codes and text that remain readable. When the cartridges are empty, just return them for recycling.

Fits Your Environment

With more connectivity options and a small footprint, the HC100 printer works with your network and fits your workspace.



Prints Wristbands for:

- **Patient identification in:**
 - » Hospitals
 - » Outpatient clinics
- **Guest identification at:**
 - » Amusement parks
 - » Water parks
 - » Resorts
 - » Carnivals
 - » Concerts
 - » Sporting events
 - » Zoos



Specifications at a Glance*

Standard Features

- Print method: Direct thermal
- Programming language: ZPL®
- Construction: Dual-wall frame, impact resistant plastic
- Quick & easy wristband cartridge loading
- Instant media calibration—no wasted media
- 32 bit RISC processor
- Zebra E³™ Printhead Energy Control
- Odometer for print length tracking
- Illuminated media low/media out indicator
- Tool-less printhead and platen replacement
- Unicode™ compliant for multi-language printing
- XML-Enabled printing—allows XML communications from information systems
- Standard tear-off mode feature
- Dual communications interface: Serial & USB

Printer Specifications

Resolution

300 dpi/12 dots per mm

Memory

8 MB Flash, 16 MB SDRAM

Print Width

3 wristband widths:

- 0.75"/19 mm
- 1"/25 mm
- 1.1875"/30 mm

Maximum Print Length

22"/558 mm

Print Speed

2"/51 mm per second

Media Sensors

Headup, media low and media out sensors

Media Characteristics

Media types

Wristband Cartridges

Operating Characteristics

Environmental

- Operating temperature: 40° F/4.4° C to 104° F/40° C
- Storage temperature: -40° F/-40° C to 140° F/60° C
- Operating humidity: 20%-85% non-condensing
- Storage humidity: 5%-85% non-condensing

Electrical

Universal power supply (PFC Compliant) 100-240VAC, 50-60Hz (70 Watts) External Power Supply

Agency Approvals

- Emissions: FCC Part 15, Subpart B, VCCI, C-Tick
- Emissions and Susceptibility: (CE): EN55022 Class-B, and EN55024
- Safety: CB Scheme IEC 60950-1:2001, TUV NRTL
- Power Supply: IEC 60601-1:1995

Physical Characteristics

- Width: 5"/127 mm
- Height: 7"/178 mm
- Depth: 9.5"/242 mm
- Weight: 3.1 lbs/1.4 kg

ZebraLink™ Solutions

Software

- ZebraDesigner™ Pro (option)
- ZebraDesigner (standard)
- ZebraDesigner for XML
- ZebraNet™ Bridge Enterprise (option)
- ZebraNet Utilities v7.0 (standard)
- ZebraDesigner Driver
- Zebra Universal Driver
- ZBI 2.0™ (option)
- ZBI-Developer™ (standard with ZBI 2.0)

Networking Options

- 10/100 Internal Ethernet—Factory-installed only, offered in combination with serial/USB interface

Firmware

- ZPL II®—Universal language for Zebra printers. Simplifies wristband and label formatting and enables format compatibility with existing systems that run Zebra printers.

Fonts and Graphics

- 16 resident expandable bitmap fonts
- One resident scalable font

Bar Code Symbolologies

- Bar Code Ratios: 2:1 (non-rotated) and 3:1
- Linear Bar Codes: Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, EAN-14, UPC-A and UPC-E with EAN 2 or 5 digit extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar, and GS1 DataBar (formerly RSS)
- 2-Dimensional: PDF417, MicroPDF417, Code 49, Maxicode, Codablock, Data Matrix, QR code, and Aztec
- Contains UFST® from Monotype Imaging, Inc.

Communication and Interface Capabilities

- RS-232 Serial interface, DB-9
- USB 2.0
- 10/100 Internal Ethernet—Factory-only installation (option)

Options and Accessories

- 10/100 Internal Ethernet—Factory-installed only, offered in combination with serial/USB interface
- Font Packs—Asian and other international font kits
- Factory-installed 64 MB (58 MB user available) Flash memory option
- ZBI 2.0—Factory- or field-installed

*Specifications subject to change without notice.
©2011 ZIH Corp. ZebraLink, E³ and all product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZebraNet, Z-Band, ZPL and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Unicode is a trademark of Unicode, Inc. Windows, Windows NT and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. UFST is a trademark of Monotype Imaging Inc. and may be registered in certain jurisdictions. All other trademarks are the property of their respective owners.

Genuine Zebra™ Wristbands for the HC100 Printer

Healthcare Wristbands

Zebra's Z-Band thermal wristbands allow you to print patient information and bar codes directly on the wristbands; no need for labels and wristband assembly inherent to laser technology.

- Determined MR-Safe by an independent MRI testing company
- Feature a silver antimicrobial coating that protects the wristband
- Scannable up to 14 days, promoting quality patient care and safety
- Quick and easy to print and fasten using an adhesive tab or color clip

Attraction and Amusement Wristbands

Enable cashless point of sale and access management with print-on-demand bar coded wristbands. A Zebra® bar code printer and direct thermal Z-Band Fun or Z-Band Splash wristbands can:

- Reduce ticket fraud; revenue losses associated with theft
- Improve transaction speeds
- Enhance each guest's experience
- Lower total cost of ownership compared to RFID wristbanding



www.zebra.com

Corporate Headquarters

+1 800 423 0442

Email: inquiry4@zebra.com

Asia-Pacific Headquarters

+65 6858 0722

Email: apacchannelmarketing@zebra.com

EMEA Headquarters

+44 (0)1628 556000

Email: mseurope@zebra.com

Latin America Headquarters

+1 847 955 2283

Email: inquiry4@zebra.com

Other Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Japan, Malaysia, South Korea, Singapore, Thailand **Latin America:** Brazil, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

GSA#: GS-35F-0268N
P1032322 Rev. 1 (9/11)